

# Rental Compressor Fleet

Electric Compressors : Aftercooled / 460v						
HP Rating	CFM	Rated PSI	Dimensions H/W/L (in)	Weight	FLA	
100	494	125	98   60   72	6500	116	
150	721	125	122 / 67 / 81	9000	170	
200	935	125	122 / 67 / 81	10800	230	
300	1502	100	140 / 75 / 91	14645	338	
Electric Compressors : Oil Free / 460v						
HP Rating	CFM	Rated PSI	Dimensions H/W/L (in)	Weight	FLA	
100	412	135	109   72.5   100	8700	130	
125	533	135	109 / 72.5 / 100	8700	161	
150	616	135	109 / 72.5 / 100	8700	184	
175	728	125	109 / 72.5 / 100	8700	212	
200	812	125	109 / 72.5 / 100	8700	235	
400	1550	150	96 / 90 / 202	13,500	800	
Diesel Compressors : Instrument Quality or 99.9% Oil Free						
CFM	PSI	Tank Capacity	Dimensions H/W/L (in)	Weight	GPH	
375	200	56	156   77   74	4440	6.55	
400	200	58	152 / 72 / 69	4045	6.55	
900	150	120	191 / 87 / 83	10045	13.6	
1600	150	190	240 / 88 / 92	16350	26.3	
Diesel Compressors: High Pressure and Aftercooled						
CFM	PSI	Tank Capacity	Dimensions H/W/L (in)	Weight	GPH	
900	500	190	240   88   92	16040	27	
1150	350	190	240 / 88 / 92	16040	27	
Dehumidification						
CFM	FLA @ 460v	Duct Size	Dimensions H/W/L (in)	Weight (lbs)		
2400	44	20" S&R	89   35   63	1250		
5000	94	20" S&R	96 / 46 / 76	2350		
Diesel Power Generation						
KW	Voltages	Tank Capacity	Dimensions H/W/L (in)	Weight	GPH	
35	208/460v	149	114   45   74	4788	2.1	
60	208/460v	173	206 / 83 / 100	8300	4.4	
100	208/460v	193	125 / 45 / 74	6996	7	
200	208/460v	400	246 / 100 / 113	13690	17.1	
Air Conditioners						
Type	Tonnage	CFM	Dimensions H/W/L (in)	Weight	FLA	Duct # & Size
Industrial	12t	4000	96   35   72	2200	28.7	2xS, 2xR, 12"
Industrial	20t	2800	107   80   94	4500	51	1x20"S, 2x20R
Industrial	30t	10000	96   66   102	3820	67	2x20"S, SxR
Industrial	40t	6400	93   88   100	7200	82	2xS, 2xR, 20"
Commercial	40t	14000	197   92   79	8300	98.2AC/255H	4xS, 6xR, 20"