

# Rental Dryer Fleet

Desiccant Dryers						
Model	Capacity (SCFM) @ 100 psig	Dryer Connection		Dimensions H/W/L (in)	Weight	
FR800	800	2" Boss		83   60   80	3200	
RD1550	1550	3" Boss		96   78   96	5000	
RD1550G	1550	3" Boss		79   83   78	5000	
RD3000	3000	2 x 3" Boss		81   91   115	9200	
RD5400	5400	4 x 3" Boss		81   91   153	16,000	
Desiccant Dryers: Air Driven Fan Motor Aftercooler Mounted						
Model	Capacity (SCFM) @ 100 psig	Dryer Connection		Dimensions H/W/L (in)	Weight	
RD450AC	450	2" Boss		82   50   69	2200	
FR800AC	800	2" Boss		80   60   80	3200	
RD1000AC	1000	2" Boss		80   75   71	3800	
RD1550AC	1550	3" Boss		96   73   97	6000	
High Pressure Desiccant Dryers						
Model	Capacity (SCFM) @ 350 psig	Dryer Connection		Dimensions H/W/L (in)	Weight	
RDH715	1200	2" Boss		96   78   96	4000	
RDH1000	1800	2" Boss		90   78   83	4500	
RDH1550	2800	2 x 2" Boss / 3" Boss		79   78   83	6150	
RDH3000	5000	2 x 3" Boss		90   87   116	12,000	
High Pressure Desiccant Dryers: Air Driven Fan Motor Aftercooler Mounted						
Model	Capacity (SCFM) @ 350 psig	Dryer Connection		Dimensions H/W/L (in)	Weight	
RDH715AC	1200	2" Boss		96   78   96	4500	
Filter Packages						
Model	Capacity (SCFM) @ 350 psig	Dryer Connection		Dimensions H/W/L (in)	Weight	
FS1600	1600	3" Boss		66   48   90	400	
ME1800	1800	3" Boss		84   48   60	800	
Air Receiver Tanks						
Model	Capacity	Max Rating		Dimensions H/W/L (in)	Weight	
T660	660 Gallons	165 psig		60   48   130	1700	
T660	660 Gallons	165 psig		60   48   130	1700	
T1060	1060 Gallons	165 psig		60   48   144	3300	
T1500	1550 Gallons	165 psig		68   54   165	4000	
Heat Exchangers						
Type	Sq Ft	Plates or Tubes	Shell	Dimensions H/W/L (in)	Nozzle Sizes	Weight
Shell & Plate	300	500F & 350psi	500F & 150psi	38" / 40" / 66"	4" Both Sides	4200
Shell & Plate	600	500F & 350psi	500F & 150psi	50" / 40" / 66"	4" P, 8" S	4200
Shell & Tube	250	500F & 500psi	500F & 500psi	19'5" / 36" / 18"	4" Both Sides	4200
Accessories						
Air Hose	2" and 3" in 10' / 25' / 50' sections					
Power Cable	4/0 x 50' Camlock - 2/4 x 50' Camlock - 2/5 x 50' Camlock					
I-lines	400amp / 800amp / 1200amp / 2000amp / 3000amp					
KVA	1000kva / 1500kva / 2500kva					